

CURLOPT_SSH_HOST_PUBLIC_KEY_MD5(3) easy_setopt op **CURLOPT_SSH_HOST_PUBLIC_KEY_MD5(3)**

NAME

CURLOPT_SSH_HOST_PUBLIC_KEY_MD5 – checksum of SSH server public key

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_SSH_HOST_PUBLIC_KEY_MD5,  
                           char *md5);
```

DESCRIPTION

Pass a char * pointing to a string containing 32 hexadecimal digits. The string should be the 128 bit MD5 checksum of the remote host's public key, and libcurl will reject the connection to the host unless the md5sums match.

DEFAULT

NULL

PROTOCOLS

SCP and SFTP

EXAMPLE

TODO

AVAILABILITY

Added in 7.17.1

RETURN VALUE

Returns **CURLE_OK** if the option is supported, **CURLE_UNKNOWN_OPTION** if not, or **CURLE_OUT_OF_MEMORY** if there was insufficient heap space.

SEE ALSO

CURLOPT_SSH_PUBLIC_KEYFILE(3), **CURLOPT_SSH_AUTH_TYPES(3)**,